



# LED TOWER LIGHT

SAAL25/TW

## HIGH PERFORMANCE ATEX LIGHTING TOWER

The SA LUMIN LED Tower Light is a rugged fully ATEX & IECEx certified transportable light, providing high quality illumination for medium to large sized areas with a powerful spread of light. With an integrated manual hand trolley and 5m transportable mast, the SA LUMIN LED Tower Light can be easily positioned and maneuvered to accommodate your needs. The adjustable light head with secure positioning bolt allows efficient angling of the light in both upwards and downwards directions.



### BENEFITS

- EX Certified for Zones 1 and 2 (Gas), 21 and 22 (Dust)
- Light output 30,000 lumens
- -50°C to +50°C Operating Temperature (Based on Plug Type)
- Easy plug-and-play application
- 6000K+ colour temperature
- Large spread of high power light
- Durable construction
- Safety cord for additional protection
- 5 year product warranty

### SPECIFICATIONS

#### CERTIFICATION

II 2 G D  
EX db eb mb IIB T4 Gb  
EX tb IIIC T104°C Db

#### INGRESS PROTECTION

IP66

#### VOLTAGE OPTIONS

110VAC, 230VAC

#### PLUG OPTIONS

ATX, CEAG, Stahl

#### OPERATING TEMPERATURE

-50°C to +50°C

#### LIGHT OUTPUT

30,000 lumens

#### LIGHT SOURCE

High Power LEDs

#### DIMENSIONS

Light Head  
460mm x 385mm x 850mm

Mast Extended  
2150mm x 2150mm x 5500mm

Mast Folded  
300mm x 300mm x 1750mm

#### WEIGHT

105kg [Excluding cable and plug]

### CORE PRODUCT INFORMATION

**SA LUMIN EX LED Tower Light 110V**  
c/w CEAG plug and 20m of braided cable  
Order Code: SAAL25-110/TW/CEA/20HRE



**SA LUMIN EX LED Tower Light 230V**  
c/w CEAG plug and 20m of braided cable  
Order Code: SAAL25-230/TW/CEA/20HRE



**Trolley for SA LUMIN Tower Light**  
Order Code: SAAL/TR



Different combinations of plugs and cable lengths also available – please contact SA Equip for more details.



LIGHT